



www.adesso.com

NuScan™ 4000 Bluetooth Wireless Barcode Scanner



Whether it is hard-to-reach barcodes or a need for mobility, the NuScan 4000 is a barcode scanner designed to simplify your job and allow you to be more productive. Equipped with a Class II Bluetooth receiver that provides a reliable 30m wireless data transfer range, the lightweight scanner is perfect for warehouses repair shops, factories, libraries and many other facilities. The scanner's laser diode scans at a rate of 100 scans per second with precision and ease. The NuScan 4000 comes with a patented cradle that helps extend battery life, giving you enough power to do 25,000 scans before another recharge is necessary.

■ Class II Bluetooth® Wireless Technology

Each read scan instantly transfers your scanned data over a range of 30m to your computer without the hassle of cords.

■ Cradle, Charger & Receiver

The 3 in one cradle, charger and receiver helps extend battery life and function as a stand for hands-free scanning.

■ Advanced Built-in Laser Engine

The 650 nm laser diode lets you scan with precision and accuracy at an operating distance of 216 mm from the barcode and will read up to 100 scans per second.

■ Direct Input

Your scans will automatically input data into common applications such as MS Excel/Word when you have them open, all without installing any software.

■ Superior Mobility


A lightweight and compact design perfect for on-the-go scanning situations.

■ Wide Symbology Compatibility

Supports over 20 different kinds of barcode symbologies, letting you scan multiple types of barcodes with one pass.



Portable



Class II Bluetooth®
Wireless Technology



Cradle, Charger
& Receiver



Wide Symbology
Compatibility

Operational Specifications:

Light Source	650 nm Laser Diode
Depth of Field	400 mm
Scan Speed	100 scans / sec
Read Angle	38°
Radio Range (open area)	30 m
Communication	Bluetooth 2.0 Compliant
Best Resolution	0.1 mm (4 mils) - Code 39
Memory size	1MB (Saves 75,000 sets EAN-13 Barcodes)
Print Contrast	45% or more
Indicators	Green/Red LED & Beeper
Interface	USB (RS232 Data Format), USB (HID)

Electrical Specifications:

Battery Type	AA NiMH rechargeable battery 1.2V x 2 (2.4 V 2500mAH)
Input Voltage	5 V DC ± 0.5 V
Charge Time	4 ~ 5 hours
Scans per Charge	15,000 scans when fully charged
Regulation	FCC Class B, CE, IEC60825 Class I

Environment Specifications:

Operating Temperature	0° C to 50° C
Operating Humidity	10% to 85% relative humidity, non-condensing
Shock Resistance	Withstand 1.2 m drop on Concrete

Physical Specifications:

Dimension (scanner only)	3.5 x 2.4 x 6.3" (90 x 60 x 160 mm)
Weight	0.34 lbs/155 g (for scanner), 0.5 lbs/225 g (for cradle)

Supported Symbologies

Code 128, coda bar, interleave 25, Industrial 25, matrix 25, China postage, UPC-A, UPC-E, EAN-13, EAN-8, code11, code 39, code 32, code 93, ...

Includes:

- NuScan 4000
- Scanner Cradle Holder
- (2) AA NiMH rechargeable 1.2V battery
- Quick Start Guide

Shipping Information:

Item	UPC Code	Box Dimensions	Box Wt.	Qty/Ctn
NuScan 4000	783750004473			10

